

Plastic foot batten



Suitable for irrigation of almost all field and vegetable crops.

Technical Specifications

- Working pressure: 0.5 - 4 kg/cm²
- Pipe Size OD: 40mm/50mm/63mm/75mm
- Riser connection Size: ½" & ¾" Female threaded

Plastic Foot Batten Features

- Suitable for ½" & ¾" sprinkler installation at the riser stand.
- Stabilizer designed for excellent gripping in the field with minimal riser vibration.
- O-ring in saddle avoid leakage at minimum pressure.
- Fast installation and easy to use in the field.
- Saddle with SS ring and metal inserted thread bush as optional model.
- Polypropylene material gives excellent strength and flexibility to achieve excellent functionality.
- UV resistant material for long life.

Modular Riser Features

- Injection moulded PP riser for long life.
- One end ¾" male threaded, another end ¾" female threaded.
- Height of plastic riser 420mm, easy to extend length by screw each other.
- This is designed to handle operating pressure upto 4 bar.
- O-ring at the root of male threaded connection, for no leakage at pressure.
- No Pipe wrench required to tighten risers.

Sr. No.	Model No.	Description
1	HT-FB63P	63mm Plastic Saddle Stabilizer With Plastic Bush
2	HT-FB75P	75mm Plastic Saddle Stabilizer With Plastic Bush
3	HT-FB63M	63mm Plastic Saddle Stabilizer With Metal Bush
4	HT-FB75M	75mm Plastic Saddle Stabilizer With Metal Bush

Universal Adopter



Features

- One end have two threads connection gives end user multi choice.
- Another end have either 1/2" or 3/4" as per requirement.
- Glass reinforced polypropylene material for socket strength.
- At higher pressure the socket will not come out from riser.
- Applying high torque during tightening, No cracks developed.
- UV & chemical resistant for durability.

Technical Specifications

- Two Sockets available as per threads connection
(3/4"/1") x 1/2"
(3/4"/1") x 3/4"
- Max. working Pressure upto 6bar

Sr. No.	Description
1	1/2" Universal Adaptor
2	3/4" Universal Adaptor

Quick Coupling Sockets



for the easy installation of $\frac{3}{4}$ "
impact sprinkler on Riser.

Features

- Available in $\frac{3}{4}$ " connection.
- 2 part design.
- Made of Engineering plastic for long life.
- Turn & Lock design without leakage during running.
- Fast & easy couple sprinklers on riser.

Sr. No.	Model No.	Descriptions
1	HT-422FS	$\frac{3}{4}$ " Female x Female Socket
2	HT-46QC	$\frac{3}{4}$ " Quick Coupling Socket